




DIN 7980

Standard withdrawn

430-530 HV



BN 774

Split spring lock washers

for screws with cylindrical head

Spring steel 430-530 HV

zinc plated blue

- ~CSN 021740



ISO 4042

Fasteners hardness ≥ 320 HV with electroplated coatings:
Susceptible to hydrogen embrittlement!
Further notice to residual risks can be found in the
introduction section.



Other coatings on request.

Article#		d ₁ min.	d ₁ max.	d ₂ max.	s
1277235	M3	3,1	3,4	5,6	1
1277243	M4	4,1	4,4	7	1,2
1277251	M5	5,1	5,4	8,8	1,6
1277278	M6	6,1	6,5	9,9	1,6
1277286	M8	8,1	8,5	12,7	2
1277294	M10	10,2	10,7	16	2,5
1277308	M12	12,2	12,7	18	2,5
1277316	M14	14,2	14,7	21,1	3
1277324	M16	16,2	17	24,4	3,5
1277332	M18	18,2	19	26,4	3,5
1277340	M20	20,2	21,2	30,6	4,5
1437089	M22	22,5	23,5	32,9	4,5
1437097	M24	24,5	25,5	35,9	5
1437100	M27	27,5	28,5	38,9	5
1437119	M30	30,5	31,7	44,1	6
1437127	M36	36,5	37,7	52,2	7