

**BN 31107****Round head square neck bolts**

without hex nuts

Stainless steel A4

- ~UNI 5732
- ~CSN 021319



At manufacturer's option, the diameter of the shaft may correspond with the pitch diameter

b: the partially threaded version can not always be guaranteed

Article#	d ₁	d ₂ max.	k max.	f max.	v max.	b~	L
3212532	M5	13,55	3,3	4,1	5,48	8	16
3212539						12	20
3212533							25
3212534							30
3212540						16	35
3212536							40
5806080	M6	16,55	3,88	4,6	6,48	8	16
5806090						10	20
5400389						15	25
5400390						18	30
5806100							35
5400391							40
5806110							45
5400392							50
5400393							60
5806120							70
5806130							75
5400394							80
5806140							90
5806150							100
5806160							120
5806170	M8	20,65	4,88	5,6	8,58	8	16
5806180							20
5400395						13	25
5400396						18	30
5806190						22	35

b: the partially threaded version can not always be guaranteed

Article#	d ₁	d ₂ max.	k max.	f max.	v max.	b~	L
5400397	M8	20,65	4,88	5,6	8,58	22	40
5806200							45
5400398							50
3205650							55
5402507							60
5806210							65
5806220							70
5806230							75
5400399							80
5806240							90
5400400							100
5806250							110
5806260							120
5806270	M10	24,65	5,38	6,6	10,58	11	20
5400401							25
5400402						16	30
5806280						21	35
5400403						26	40
3257077							45
5400404							50
5400405							60
5806290							70
5400406							80
5806300							90
5402508							100
5806310							110
5806320							120
5806330						32	130
5806340							140
5806350							150
5806360	M12	30,65	6,95	8,75	12,7	12	30
5806370						17	35
5806380						22	40
5806390						27	45
5806400						30	50
5806410							60
5806420							70
5806430							80
5806440							90
5806450							100
5806460							110

b: the partially threaded version can not always be guaranteed

Article#	d ₁	d ₂ max.	k max.	f max.	v max.	b~	L
5806470	M12	30,65	6,95	8,75	12,7	30	120
5806480							130
5806490							140
5806500							150